


Coaxial Cable, Plenum



| Part No. | Description | AWG | Conductor | Shield | Ohms | Nom. O.D. (in) | Weight (lbs/M-ft) |
|-------------|-----------------|-----|---|-------------------------------|------|-------------------|----------------------|
| 1C22W162AUP | RG-62 | 22 | Solid CCS | 96% BC Braid | 93 | .200 | 40 |
| 1C22W11BMP | RG-62 IBM | 22 | Solid CCS | 96% BC Braid | 93 | .200 | 42 |
| 1C20W159UP | RG-59 | 20 | Solid CCS | 95% BC Braid | 75 | .196 | 36 |
| 2C22W159USP | RG-59 Dual Wang | 22 | Solid CCS | 97% BC Braid | 75 | .212 x .424 | 98 |
| 1C20B158UP | RG-58 | 20 | Solid BC | 95% TC Braid | 53.5 | .161 | 35 |
| 1C14B111UP | RG-11 | 14 | Solid BC | Foil + 95% TC Braid | 75 | .352 | 115 |
| 1C18B16UP1 | RG-6 | 18 | Solid BC | Foil + 95% TC Braid | 75 | .240 | 44 |
| 1C18B16UP | RG-6 | 18 | Solid BC | 95% BC Braid | 75 | .228 | 43 |
| 1C20B159UP | RG-59 | 20 | Solid BC | 95% BC Braid | 75 | .193 | 31 |
| 1C12B1NETP | Ethernet | 12 | Solid BC | Foil + 90% TC Braid | 50 | .247 | 148 |
| 1C20T19NETP | Thin Net | 20 | Stranded TC | Foil + 93% TC Braid | 50 | .165 | 30 |
| 1P20X7TWAXP | Twinax | 20 | Stranded 1-TC, 1-BC | Foil + 85% TC Braid | 100 | .267 | 45 |
| 3C22X759UP | Siamese | 22 | 1 pr. 22 AWG Stranded TC, Stranded BC | Pair Shielded 95% TC Braid | 75 | .210 x .359 | 45 |

Coaxial Cable, Armored

Armored coaxial cable features PVC inner and outer jackets with corrugated aluminum armor between.

| Part No. | Description | AWG | Conductor | Shield | Ohms | Jacket | Nom. O.D. (in) | Weight (lbs/M-ft) |
|-------------|-------------|-----|-------------|---------------------|------|--------|-------------------|----------------------|
| 2C20T7TWAXA | Blue Hose | 20 | Stranded TC | Foil + 55% TC Braid | 78 | PVC | .563 | 122 |