

Telephone Test Set Comparison



	TS®52 PRO	TS®44 PRO	TS®42DLX	TS®22A	TS®22	TS®25D	TS®30 / TS®120*	TS®19
Caller-ID verification	•					•		
LCD-Liquid Crystal Display	•					•		
Backlit LCD with Glow-in-the-Dark keypad	•							
DTMF Digit Grabbing	•					•		
Extended range high-impedance DataSafe operation in monitor mode	•	•	•			•		
High-impedance DataSafe operation in monitor mode	•	•	•	•		•	•	•
Data lockout protection	•	•				•		
Data lockout override	•	•				•		
DSL/POTS filtering technology	•	•	•			•		
Low/high voltage indication	•	•	•			•		
Current (mA) indication	•	•	•			•		
Over voltage protection	•	•	•	•	•	•	•	
Over current protection	•	•	•	•	•	•	•	
Two-way speakerphone for true hands-free conversations	•	•	•	•				
One-way amplified speaker for hands-free monitoring	•	•	•	•	•	•		
Audible ringer for callbacks	•	•	•	•	•	•	•	•
Weatherproof – exceeds American Military Spec. MIL-STD-810E	•	•	•					
RainSafe – safe in severe weather conditions	•	•	•	•	•		•	
DropSafe – passes 20 foot (6 meter) drop test onto concrete	•	•	•	•	•		•	
Meets Bellcore specifications	•	•	•	•	•		•	
Tone and pulse operation	•	•	•	•	•	•	•	•
Polarity indication	•	•	•	•	•	•	•	•
PBX pause button	•	•	•	•	•	•		
Stores at least nine 18-digit numbers in repertory dialer (speed dialing)	•	•	•	•	•	•		
Replaceable 9V battery	•	•	•	•	•	•		
Visual ANAC (Automatic Number Announcement Circuit) mode option. Not available in all regions	•							

www.flukenetworks.com/testsets

*The TS25D includes tone generator mode and talk battery supply mode. The TS120 designed for outside North America only. 67/33 break/make ratio.